

## Xerox<sup>®</sup> VersaLink<sup>®</sup> C600 Colour Printer

VersaLink C600 Colour Printers are built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to www.ConnectKey.com.



SYSTEM SPECIFICATIONS	VERSALINK 600/DN
<b>One-sided Speed<sup>1</sup></b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 55 ppm colour and black-and-white Up to 53 ppm colour and black-and-white Up to 45 ppm colour and black-and-white
<b>Two-sided Speed<sup>1</sup></b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 52 ppm colour and black-and-white Up to 50 ppm colour and black-and-white Up to 26 ppm colour and black-and-white
Monthly Duty Cycle <sup>2</sup>	Up to 120,000 pages / month
Recommended Average Monthly Print Volume <sup>3</sup>	Up to 17,000 pages
Hard Drive	Optional 320 GB HDD
Processor	1.05 GHz
Memory	2 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127V +/-10% Frequency: 50/60 Hz +/-3%, 12A			
Europe and Other Geographies	Voltage: 220-240V +/- 1 Frequency: 50/60 Hz +/-			
POWER CONSUMPTION				
Continuous Printing <sup>4</sup>	800 watts or less			
Ready / Standby Mode <sup>4</sup>	85 watts or less			
Energy Saver / Sleep Mode <sup>4</sup>	0.7 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)			
Required Temperature Range (Operating)	50° to 90° F (10° to 32° C)			
Required Relative Humidity	15% to 85%			
<b>Sound Power Levels</b> Operating Standby	7.27 B(A) or less 4.84 B(A) or less			
Sound Pressure Levels Operating Standby	57.4 dB(A) or less, 33.5 dB(A) or less			
Boot Time (from Off to UI Ready)	As fast as 52 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 11 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH DEPTH HEIGHT WEIGHT			
Base Unit	16.9 in. / 427.4 mm	18.4 in. / 465.5 mm	17.5 in. / 443.4 mm	64.8 lb. / 29.4 kg
Base Unit with Additional 550-sheet Tray	16.9 in. / 427.4 mm         18.4 in. / 465.5 mm         22.3 in. / 566.4 mm         79.4 lb. / 36 kg			
Base Unit with High Capacity Feeder	28.5 in. / 724.2 mm 30.4 in. / 772.1 mm 35.5 in. / 902.4 mm 108.2 lb. / 49.1 kg			
Base Unit with High Capacity Feeder and Finisher	28.5 in. / 724.2 mm 30.4 in. / 772.1 mm 44.2 in. / 1121 mm 123.2 lb. / 55.9 kg			
Base Unit with High Capacity Feeder and Mailbox	28.5 in. / 724.2 mm 30.4 in. / 772.1 mm 44.2 in. / 1121 mm 119.9 lb. / 54.4 kg			
550-sheet Paper Tray	16.5 in. / 420 mm	18.3 in. / 464.5 mm	4.8 in. / 123 mm	4.1 lb. / 6.6 kg
High Capacity Feeder	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	18.1 in. / 459 mm	43.4 lb. / 19.7 kg
Cabinet	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	13.2 in. / 336 mm	37 lb. / 16.6 kg
Stand / Caster Base	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	3.5 in. / 90 mm	18.7 lb. / 8.5 kg
Mailbox	17.7 in. / 450.8 mm 18.8 in. / 477.6 mm 9.8 in. / 248.0 mm 11.7 lb. / 5.3 kg			
Finisher	17.7 in. / 450.8 mm 16.2 in. / 411.0 mm 9.8 in. / 248.0 mm 15 lb. / 6.8 kg			

## Xerox<sup>®</sup> VersaLink<sup>®</sup> C600 Colour Printer

DIMENSIONS AND WEIGHT	WIDTH	DEPTH	HEIGHT	WEIGHT
(PACKAGED)				
Base Unit	22.8 in. / 580 mm	25 in. / 634 mm	23.9 in. / 607 mm	77.2 lb. / 35 kg
550-sheet Paper Tray	21.1 in. / 535 mm	23 in. / 584 mm	9.8 in. / 248 mm	18.7 lb. / 8.5 kg
High Capacity Feeder (includes Caster Base)	22.4 in. / 568 mm	26.1 in. / 663 mm	28 in. / 711 mm	83.8 lb. / 38 kg
Cabinet (includes Caster Base)	23 in. / 584 mm	24.8 in. / 629 mm	23.5 in. / 597 mm	57.3 lb. / 28 kg
Caster Base	23 in. / 585 mm	24.4 in. / 619 mm	13 in. / 330 mm	39.7 lb. / 18 kg
Mailbox	22.6 in. / 573 mm	20.4 in. / 518 mm	15.2 in. / 386 mm	16.3 lb. / 7.8 kg
Finisher	22.6 in. / 573 mm	15.7 in. / 398 mm	15.2 in. / 386 mm	18.6 lb. / 8.8 kg
CERTIFICATIONS				
	To view the latest list	of certifications, go to <b>ww</b> y	v.xerox.com/OfficeCertifi	ications.
PRINT	ł			
First-print-out Time	As fast as 8 seconds c	olour and black-and-white		
Print Resolution	Up to 1200 x 2400 dp	i		
Page Description Languages	PCL <sup>®</sup> 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe <sup>®</sup> PostScript <sup>®</sup> 3™			
Maximum Print Area	4 mm from edge of paper			
Print Features	4 mm from edge of paper         Application Defaults         Banner Pages Enable / Disable         Bi-directional Real-time Status         Booklet Layout         Color Adjustments (lightness, contrast, saturation, color balance)         Color Correction         Draft Mode         Fit to new paper size         Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)         Job Monitoring (Client or Local User Interface)         N-up Page Layout (up to 16 pages per sheet)         Paper Selection by Attribute         Personal Print         Print Around Enable / Disable         Print from USB         Run Black         Sample Set         Saved Job         Scaling         Secure Print         Skip Blank Pages         Special Pages (exception page programming: covers, inserts, exceptions pages)         Store and Recall Driver Settings         Stored Jobs Deletion         Two-sided Printing (as default – DN configuration)         Watermark (predefined and custom)         Earth Smart Driver Settings			
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A			

Operating Systems	Windows® 7, 8, 8.1, 10         Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016         macOS® 10.11, 10.12, 10.13         Citrix®         Redhat® Enterprise Linux®         Fedora Core         IBM® AIX®         HP-UX®         Oracle® Solaris         SUSE®         SAP®         Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.	
Fonts	PostScript fonts: 136 PCL fonts: 83	
Xerox <sup>®</sup> Global Print Driver <sup>®</sup>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox <sup>®</sup> and non-Xerox <sup>®</sup> devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox <sup>®</sup> Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos®and others.	
MOBILE SOLUTIONS AND MOB	ILE DEVICE APPS	
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone <sup>®</sup> or iPad <sup>®</sup> with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.	
Mopria® Certified	ConnectKey Technology-enabled print devices are Mopria <sup>®</sup> certified. Mopria <sup>®</sup> certification ensures you can print wirelessly from your Mopria <sup>®</sup> supported (Android) smart phone, tablet and other mobile devices instantly and easily.	
Xerox <sup>®</sup> @printbyXerox	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.	
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	<ul> <li>The Xerox<sup>®</sup> Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers.</li> <li>You can easily print photos, Web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play<sup>™</sup> store.</li> </ul>	
Xerox <sup>®</sup> Print Management and Mobility Suite, Xerox <sup>®</sup> Print Management and Mobility Service	Xerox <sup>®</sup> Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.	
SOFTWARE SOLUTIONS		
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled device.	

## Xerox<sup>®</sup> VersaLink<sup>®</sup> C600 Colour Printer

SECURITY	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM) *Requires HDD/Productivity Kit
ACCOUNTING	
XEROX <sup>®</sup> STANDARD ACC	COUNTING / NETWORK ACCOUNTING (STANDARD)
Tracking	Print usage
Accounting	Xerox <sup>®</sup> Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 accounting records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS	- NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)
	<ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>

## Xerox<sup>®</sup> VersaLink<sup>®</sup> C600 Colour Printer

PAPER HANDLING				
BYPASS TRAY				
Capacity <sup>5</sup>	150 sheets			
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm			
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm			
Types	Bond Plain Paper Cardstock Custom	Envelopes Hole Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled	
TRAY 1				
Capacity <sup>5</sup>	550 sheets			
Sizes	Custom sizes: 3 x 7.5 in. to	8.5 x 14 in. / 76 x 190 mm to 216 x 35	56 mm	
<b>Weights</b> One-sided: Two-sided:		16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm		
Types	Bond Plain Paper Cardstock Custom	Hole Punched Labels Letterhead Lightweight Cardstock	Heavyweight Cardstock Pre-Printed Recycled	
UP TO FOUR ADDITIONAL TRAY	YS (OPTIONAL)			
Capacity <sup>5</sup>	550 sheets			
Sizes	Custom sizes: 3 x 7.5 in. to	98.5 x 14 in. / 76 x 190 mm to 216 x 35	56 mm	
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm			
Types	Bond Plain Paper Cardstock Custom	Hole Punched Labels Letterhead Lightweight Cardstock	Heavyweight Cardstock Pre-Printed Recycled	
HIGH CAPACITY FEEDER (OPTIC	ONAL – ONLY ONE ADDIT	IONAL 550-SHEET TRAY CAN BE AD	DED TO HIGH CAPACITY FEEDER)	
Capacity <sup>5</sup>	2,000 sheets			
Sizes	Letter/A4			
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 65 lb. cover 16 lb. bond to 65 lb. cover			
Туреѕ	Bond Plain Paper Hole Punched	Letterhead Lightweight Cardstock	Pre-Printed Recycled	
TOTAL CAPACITY				
Standard Device Capacity <sup>5</sup>	700 sheets			
Maximum Device Capacity <sup>5</sup>	3,250 sheets			
PAPER OUTPUT / FINISHING				
Capacity <sup>5</sup>	Up to 500 sheets			
Automatic Two-sided Printing	Standard			
FINISHER (OPTIONAL)				
Capacity <sup>5</sup>	500-sheet tray, 50-sheet s	staplina		

MAILBOX (OPTIONAL)			
<b>Capacity</b> <sup>5</sup>	Four 100-sheet bins		
DEVICE MANAGEMENT			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour <sup>®</sup> / AirPrint <sup>™</sup> Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS		
REMOTE CONTROL PANEL			
	<ul> <li>Enables faster, more convenient technical support and user training</li> <li>IT administrators and other authorized users can control the device remotely from a web page on any device</li> <li>Remote user experience is identical to performing tasks directly at the device</li> </ul>		
XEROX <sup>®</sup> CENTREWARE <sup>®</sup> WEB	SOFTWARE		
	<ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>		
XEROX <sup>®</sup> EMBEDDED WEB SER	VER – INTEGRATED DEVICE WEB PAGE		
Device Status	<ul> <li>Tray status/contents</li> <li>Consumables status</li> <li>Billing/Usage</li> <li>Quick Links</li> <li>Online Support</li> </ul>		
Print Queue Viewing	Job print queue management—view and delete		
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Microsoft <sup>®</sup> Internet Explorer <sup>®</sup> Microsoft Edge <sup>™</sup> Mozilla <sup>™</sup> Firefox <sup>®</sup> Apple <sup>®</sup> Safari <sup>®</sup> Google Chrome <sup>™</sup>		
REMOTE SERVICES			
Xerox <sup>®</sup> Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox <sup>®</sup> device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox <sup>®</sup> Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
WHAT'S IN THE BOX			
	VersaLink C600 Colour Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 6,000 print capacity <sup>6</sup> , Black: 10,000 print capacity <sup>6</sup> Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord		

SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Print Cartridges	Black: 6,000 standard pages <sup>6</sup> Cyan: 6,000 standard pages <sup>6</sup> Magenta: 6,000 standard pages <sup>6</sup> Yellow: 6,000 standard pages <sup>6</sup>	106R03911 106R03908 106R03909 106R03910
High Capacity Print Cartridges	Black: 12,200 standard pages <sup>6</sup> Cyan: 10,100 standard pages <sup>6</sup> Magenta: 10,100 standard pages <sup>6</sup> Yellow: 10,100 standard pages <sup>6</sup>	106R03915 106R03912 106R03913 106R03914
Extra High Capacity Print Cartridges	Black: 16,900 standard pages <sup>6</sup> Cyan: 16,800 standard pages <sup>6</sup> Magenta: 16,800 standard pages <sup>6</sup> Yellow: 16,800 standard pages <sup>6</sup>	106R03927 106R03924 106R03925 106R03926
ROUTINE MAINTENANCE ITEM	S	
Drum Cartridges	Cyan: 40,000 pages <sup>7</sup> Magenta: 40,000 pages <sup>7</sup> Yellow: 40,000 pages <sup>7</sup> Black: 40,000 pages <sup>7</sup>	108R01485 108R01486 108R01487 108R01488
Waste Cartridge	30,000 pages <sup>7</sup>	108R01416
ACCESSORIES		
550-sheet Feeder		097S04949
2,000-sheet High Capacity Feed	er (includes Stand/Caster Base)	097S04948
Cabinet (includes Stabilizers)		097S04994
Stand/Caster Base		097504954
Finisher (500 sheets, 50-sheet stapler)		097504952
4-Bin Mailbox (100 sheets per bin)		097504953
Productivity Kit with 320 GB HDD		497K18360
Wireless Network Adapter (Wi-Fi Kit)		497K16750

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24/34.
 <sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 <sup>3</sup> Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.
 <sup>4</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
 <sup>5</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.
 <sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.
 <sup>7</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/latest/SUPGL-01.pdf.

For more information, visit us at www.xerox.com/Office

Configurations vary by geography.

©2019 Xerox Corporation. All rights reserved. Xerox®, CentreWare®, ConnectKey®, Global Print Driver®, Mobile Express Driver®, VersaLink® and Xerox Extensible Interface Platform® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. 8/19 PN03335\_T121 BR26779 VC6SS-012F

